

Previous RM-CG Firmware version information

V1.5.0

New Functions

- When RM-CG and RM-CR are used in combination, it is now possible to change the color of the front panel indicator of RM-CG when there is no call. RM-CR and the Web GUI "RM-CR Device Manager" are required to make this change.

Improvements

- Improved the operation of the microphone beam.
 - Increased the speaker tracking speed.
 - Effectively picks up soft voices but does not easily react to noises.
- Improved the operation of the echo canceller.

V1.2.0

New Functions

- Now supports SNMP (Simple Network Management Protocol), a remote management protocol.
- Added a mute group function to link microphone muting for each group. It can be used in an environment combined with the RM-CR.

Improvements

- Improved the description of the Web GUI.

V1.1.0

New Functions

- You can now check and change parameters for digital signal processing on the [Processing] window in Web GUI. You can also now import and export settings for digital signal processing on the [Configuration] window.
- Added a command for outputting the beam direction in the Remote Control Protocol.

Fixed Bugs

- Fixed the issue in which the Web GUI [SUBMIT] button cannot be clicked.
- Fixed other small issues.

V1.0.2

New Functions

When adjusting the effective range of RM-CG tracking in the Web GUI [MICROPHONE SETTINGS], you can now drag and drop the end points (4 orange dots) of each line displayed in the [Tracking area] diagram.